



PI Model	Output Power Ratings			Prime Power		Standby Power	
	rpm	Frequency	Voltage	kVA	kWe	kVA	kWe
PI 275C	1500	50Hz	400	250	200	275	220
PI 313C	1800	60Hz	480	284	227	313	250

Applicable Standard and References: ISO 8528-1; ISO 3046-1; BS 5514-1
 The above given ratings are at 0.8 power factor (PF)

Engine Technical data				Air System				
Engine Make and Model	Cummins QSL9-G3			Air Filter Type	Dry Element (replaceable)			
Cylinders	6 Cylinder, In-Line			Combustion Air Flow m ³ /min. (cfm)	Prime	18.7 (660)		
Intake	Turbocharged, Charged Air Cooled				Standby	18.5 (655)		
Combustion System	Direct Injection			Max Air Filter Intake Restriction	3.74 Kpa			
Displacement	8.8 Lit			Lubrication System				
Governor	Electronic			Lube Oil	API CH4/CI4; SAE 15W-40			
Emission Regulation	EPA Tier 3			Lube Oil Capacity	26.5 Lit			
Electrical Starting System	24 V starter motor			Oil Pan Max/Min	24/20 Lit			
Fuel System				Cooling System				
Fuel Filter Type	Replaceable Elements			Coolant Capacity	15 L			
Recommened Fuel	Class A2 Diesel			Cooling System	Monted Radiator, Air-Air Charge Cooled			
Fuel Consumption l/hr (US gal/hr)	Standby Power	66.0	(17.30)	Fan Air Flow m ³ /min. (cfm)	474 (16739)			
	Prime Power	59.0	(15.60)	Heat Radiation to Room	Prime	20 kW		
	75% of Prime	49.0	(13.00)		Standby	20 kW		
	50% of Prime	34.0	(8.90)					
Exhaust System				Alternator Technical data		Stamford / or equivalent		
Silencer	Grade	Industrial		Model	UCI274H			
	Size	4"		N° of Poles	4	Protection	IP-23	
	Qty	1		N° of Terminals	12	Insulation Class	H	
Exhaust Gas Flow m ³ /min. (cfm)	Prime	35.3 (1247)		AVR and Excit.	SX460			
	Standby	39.3 (1388)		Regulation	+/- 1.5%			
Max Allowable Backpressure	10.2 kPa			Cooling Air Flow m ³ /min. (cfm)	34.80 (1230)			
Exhaust Gas Max. Temperature	585°C							
Controller Features		ComAp - AMF9 / DSE (optional)		Gen-set Enclosure Specification (optional)				
Controller Make and Model	Auto Mains Failure (AMF) application including remote communication, User configuration and complete gen-set monitoring and protection.			Enclosure Type	Acoustic and Weather Proof			
				Anticorrosive Protection	Polyester Powder Coated Galvanized Sheet			
Engine protection	Oil Pressure	Fuel level (option)		Ingress Protection rating	Weather Proof IP23			
	Coolant Temperature			Transportation	ISO standard lifting			
Generator Protection	Over / Under Voltage	Over Current		Noise level	65 dba @ 7 meters			
	Over / Under Frequency	Phases Sequence		Emergency Stop	External Emergency Push Botton			
	Charging Alternator Fault			Canopy RAL color	RAL 2000			
Inputs and Outputs	3 No's Configurable Analog Inputs			Chassis RAL color	RAL 9011			
	4 No's Binary Inputs			Shipping data				
	6 No's Binary Outputs			Type	Lenght (mm)	Width (mm)	Hight (mm)	Weight (kg)
Event and Performance Log	Gen-set Text Alarm Log			Open	2850	1145	2042	2300
	Engine Hours History Log			Enclosure	3991	1413	2413	3950

- Notes: 1-Prime power rating of generating set is a variable load and unlimited hours usage are applied on the generating set with an average load factor of 80% of the prime rating over each 24 hour period. Noting that a 10% overload is available for 1 hour in every 12 hours operation.
 2-Standby power rating of the generating set is a variable load limited to an annual usage upto 500 hours is applied, with 300 hours ff which may be continuous running. Noting that no overload is is permitted.
 3- Warranty: one year or (1000) hours which comes first.
 4- Referring to our company policy of continuous development, PI reserves the right to change specification without notice.