

## THE POWER OF DUBAI

PI 14.3P/50Hz PI 17.4P/60Hz

Controller Features	ComAp – AMF9 / DSE (Optional)			
Controller Make and Model	Auto Mains Failure (AMF) applications including remote communication , User configuration and complete gen-set monitoring and protection. Ready for generators with 3 ph 4 wires / 3 ph 3 wires / Mono ph			
Engine Protections	Oil pressure     Coolant temperature			
Generator Protections	Over / Under voltage     Over/Under frequency     Phases Sequence     Over/Under frequency     Charging Alternator Fault			
Inputs and Outputs	<ul> <li>3 No's Configurable analog inputs</li> <li>6 No's binary outputs</li> <li>D + Pre-Excitation terminal</li> </ul>			
Event and Performance Log	Gen-set text alarm log     For More Features We Can Use     Higher Controller			

Genset Enclosure Specification (Optional)				
Enclosure Type	Acoustic and Weather Proof			
Anticorrosive Protection	Polyester Powder Coated Galvanized Sheet			
Access Doors	4			
Drainage	Fuel &Water Drainage Provision			
Transportation	Tested Single Point Lifting Facility & Forklift Pockets			
Noise Level (@ Free-Field Conditions)	66 dBA @ 7 meter			
Water Fill	Radiator water Filling Provision			
Cable Access	Cable Inlet and Outlet provision			
Emergency Stop	External Emergency Push Button			
Canopy RAL Color	RAL 2000			
Chassis RAL Color	RAL 9011			

Shipping Data						
Туре	Length (mm)	Width (mm)	Height (mm)	Weight (kg)		
Open	1624	750	1220	419		
Enclosed	2212	912	1402	717		

## Notes:

\*Prime power rating of the generating set is where a variable load and unlimited hours usage are applied on the generating set with an average load factor of 80% of the prime rating over each 24 hour period. Noting that a 10% overload is available for 1 hour in every 12 hours operation

\*\*Standby power rating of the generating set is where a variable load limited to an annual usage upto 500 hours is applied, with 300 hours

of which may be continuous running. Noting that no overload is permitted

All generators carry a one year or (1000) hours' manufacturer's warranty

In line with our policy of continuous development, PI reserves the right to change specification without notice



Dubai I Abu Dhabi I Qatar I Oman I CIS Countries

info@pi-dubai.com | www.pi-dubai.com GPS: 25° 7' 50" N, 55° 14' 53" E

