



MODEL	rpm / Hz	VOLTAGE	PRIME ⁽¹⁾	STANDBY ⁽²⁾
PI 2250Y	1800 / 60	480/277 V	2000kVA / 1600 kWe	2250kVA / 1800kWe

Full rated power available upto 100 meter elevation at ambient of 27degC, for other temperature and altitude limits please consult application team.

ENGINE SPECIFICATIONS

Rated Output (PRP) ⁽¹⁾	1714 kW _m
Rated Output (ESP) ⁽²⁾	1894 kW _m
Engine Make & Model	YC16VTD2700-D32
No. of Cylinders	16 Vertical, V-type
Cycle	4 Strokes
Aspiration	Turbocharged, water-air intercooled
Cooling Method	Water
Governing Type	Electronic
Governing Class	ISO 8528 G3
Compression Ratio	14:01
Displacement	52.26 L
BorexStroke (mm)	152×180 mm
Battery and Charger Alternator	24V

AIR SYSTEM

Air Filter Type	Dry-type, filter cartridge of hardware cloth
Combustion Air Flow (PRP)	TBA m ³ /min
Combustion Air Flow (ESP)	TBA m ³ /min
Radiator Air Flow	N/A

COOLING SYSTEM

Total Coolant Capacity (L)	TBA L
Water Pump Type	Centrifugal Eng-Driven
Radiator Fan Load	N/A
Heat Radiation to Room (PRP)	TBA kW
Heat Radiation to Room (ESP)	TBA kW

LUBRICATION SYSTEM

Oil Filter	TBA
Total Oil Capacity	(280) L
Oil Pan low level/ high level	TBA L
Oil Type	API CH4/CI4; SAE 15W-40

FUEL SYSTEM

Fuel Filter:	
Recommended Fuel	Class A2 Diesel
Fuel Consumption Standby	492.1 L/hr
Fuel Consumption 100% PRP	443.1 L/hr
Fuel Consumption 75% PRP	332.4 L/hr
Fuel Consumption 50% PRP	232.3 L/hr

EXHAUST SYSTEM

Muffler Type	Residential grade
Max. Back Pressure	TBA kPa
Exhaust Gas Flow (PRP/ESP)	TBA m ³ /min
Exhaust Gas Temperature (PRP/ESP)	≤TBA ⁰ C/≤TBA ⁰ C

ALTERNATOR SPECIFICATIONS

Rated Output (Prime) (1)	2600 kVA
Rated Output (Standby) (2)	2706 kVA
Alternator Make & Model	Stamford S7L1D-G41
Number of Poles	4
Number of Winding Leads	6 Lead std/ 12 lead optional
Type of Bearing	Single
Insulation Class / Temp Rise	H/H
Efficiency @ Rated Voltage	96.00%
Ingress Protection Rating	IP 23
Excitation System	PMG
AVR Model	MX341

ALTERNATOR OPERATING DATA

Overspeed	2250 r.p.m
Voltage Regulation	±0.5%
Waveform distortion	NO LOAD < 1.5% NON-DISTORTING BALANCED LINEAR LOAD < 5.0%
Radio Interface	BS EN 61000-6-2 & BS EN 61000-6-4, VDE 0875G, VDE 0875N
Cooling Air Flow	2.87m ³ /sec

⁽¹⁾ **PRIME POWER RATING (PRP):** PRP is defined as the maximum power which a Generating set is capable of delivering continuously whilst supplying a variable electrical load when operated for an unlimited number of hours per year. The permissible average power output over 24 hours shall not exceed 70% of PRP unless otherwise agreed by RIC engine manufacturer. An overload capability of 10% of 100% of the prime rated electrical power is permitted for emergency use for a period of 1 hour within 12 hours of operation

⁽²⁾ **EMERGENCY STANDBY POWER RATING (ESP):** ESP is defined as the maximum power available during a variable electrical power sequence, under the stated operation condition, for which a generating set is capable of delivering power in the event of a utility power outage or under test condition for up to 200 Hours of operation per year. The permissible average output over 24 hour of operation shall not exceed 70 % of the ESP power rating noting that no over load is permitted.



CONTROLLER SPECIFICATIONS

Controller Make & Model	DeepSea 6120 MKII
Operation Mode	MRS / AMF (optional)
Display	Graphic Back-lit LCD (128x64) pixels
Ingress Protection Rating	IP65
Binary Inputs/Outputs	8 / 6
Analog Inputs	4
Measurement	Vac, A, Hz, kVA, kW, Vdc
Event Log	Alarms log, Hrs log
Communication	USB

ENCLOSURE SPECIFICATIONS

Enclosure Type	Acoustic & Weather Proof
Anticorrosive Protection	Polyester Powder Coated Galvanized Sheet
Ingress Protection Rating	IP22
Lifting	ISO Standard Lifting
Emergency	External Emergency Push Button
Canopy RAL Color	RAL 9010
Baseframe RAL Color	RAL 9011
Noise Pressure level @ 7m	88 dB(A)

GENSET DIMENSIONS & WEIGHT

GENSET TYPE	Length (mm)	Width (mm)	Height (mm)	Fuel Tank Capacity (L)	Dry Weight (kg) Appx	Wet Weight (kg) Appx
OPEN	6300	2610	2475	N/A	13000	13500
CLOSE	40 FEET HC CONTAINER			N/A	16350	16650

Note: The following dimensions are for preliminary guidance. For more detailed and accurate dimensions, please refer to the General Arrangement Drawing (GAD).

STANDARD MECHANICAL FEATURES

Genset design provides a low noise level with an optimized performance of the ventilation and exhaust systems at 50 °C ambient temperature.

Robust structure design of Enclosure and Baseframe.

Heavy duty lifting lugs.

Multi doors for easy access & maintenance.

Ingress Protection Rating according to BS EN 60529.

Heavy Duty Baseframe with built-in tank & forklift pockets.

Residential Grade Muffler with rain cap.

STANDARD ELECTRICAL FEATURES

An advanced Control system is designed to provide a comprehensive protection and to monitor the parameters of generating set.

MCCB power circuit breaker.

Battery with charging alternator, cables, and tray.

Sealed harness & high resistant electrical connections.

Fast and accurate protection response.

Generating Set remote start function.

Numeric display with LED. Various languages capable.

OPTIONAL FEATURES

Advanced Controllers are available on request.

4 poles manual / Motorized Circuit breaker

Pre heating system

Static Battery Charger

Critical grade muffler

Electronic governor

Remote Annunciator

Application

Infrastructure, Industrial, Residential, Telecom,
Defense, Mining, Agriculture

